MARKET LEADER



SOLAR LIGHTING TOWER











COST. EFFECTIVE

METRO GP43K

GENERAL

Model

Lumen Output Mast Height

Mast Type

Lights

Coverage

Light Bar Rotation

Light Bar Tilt

Trailer Type

Tyre and Rim Size

Stabiliser Supports

Mudguard / Wheel Chock

Security

Features

Metro - GP43k

43,000

7.5 Metres

Electric/Cable

4 x 100w LED Modules

130 x 120m at 3 lux

355°

70°

Single Axle

14'

4 x Manual

Included

Wheel lock / hitch lock, wheel clamp

Timer, day/night modes, jack pads,

fire extinguisher, isolators

OPERATIONAL DATA

Wind Rating

Working Temperature

100km/h

0° to 50° (-25° with optional kit)

BATTERY

Battery

Runtime

Solar

Solar Tilt

Efficiency (solar)

UNIT

Dimensions (Towing)

Dimensions (Deployed) Dimensions (Stowed)

Weight

7.7kWh Lithium

36 Hours

1.32kWp

45°

1 hour of sun/4 hours of light

3280x 1500 x 3010 (LxWxH) 2370x 3310 x 7670 (LxWxH) 2370 x 1500 x 3010 (LxWxH)

1200kg

